

# HD-162s

Stick Welding  
Power Source

## Quick Specs

### Light Industrial Applications

Maintenance Repair  
Shipboard Installation  
Farm / Ranch  
Hobbyist

### Power Voltage

1 Phase AC240V  $\pm$ 15%  
50/60Hz

### Input Current

15A/3.6kVA

### Output Current

50-120A  
Max. OCV: 55VDC

### Output Voltage

24.8V

### Duty Cycle

25%

### Weight

1.25KG

### Dimensions

D230xH230xW75MM

## Portable. Professional. Rugged. Affordable.

The inverter *HD-162s* offers much more than you would expect from a welder this size. Weighing in at just under 1.25kg the Inverter *HD-162s* is no lightweight contender. It packs the full punch of a heavyweight professional that you can take to the most demanding job sites. It can operate from a portable generator.

### FEATURES

- **Automatic Arc Force** minimizes electrode sticking in the puddle without compromising arc stability or increased spatter.
- **Automatic Hot Start** boosts the current during starting to make striking an arc easier
- **Thermal overload protection with indicator light** helps prevent machine damage if the duty cycle is exceeded or airflow is blocked.
- Inverter-based, DC power source has a **simple-to-use operator interface** providing only the necessary controls in a compact machine.

### PROCESSES

Stick (SMAW)



### INCLUDED

*HD-162s* Machine Only Includes:

- *HD-162s*
- 1.5M work cable and clamp.

### INPUT



### OUTPUT



AUSTCORP MANUFACTURING SDN. BHD.

NO. 8 & 10 PERSIARAN BATU GAJAH PERDANA 3

TAMAN BATU GAJAH PERDANA

31550 PUSING PERAK MALAYSIA

TEL: (605)3632 115 FAX: (605)3632 111

E-mail: [austcorp@welding.com.my](mailto:austcorp@welding.com.my)

WEB: [www.welding.com.my](http://www.welding.com.my)



Welding Technology