

TIG/STICK Welding Power Source

Quick Specs Light Industrial Applications
Maintenance Repair
Shipboard Installation
Fabrication
Hobbyist
Process Piping

Power Voltage 1 Phase AC240V ±15% 50/60Hz Input Current 25A/6kVA Output Current 7-200A Max. OCV: 64.6VDC Output Voltage 18V

Duty Cycle 60% Weight

9KG

Dimensions D375×H295×W155MM

Portable. Professional. Rugged. Affordable.

The inverter *VT-201S* offers much more than you would expect from a welder this size. Weighing in at just under 6kg the Inverter *VT-201S* is no lightweight contender. It packs the full punch of a heavyweight professional that you can take to the most demanding job sites. It can operate from a portable generator.

FEATURES

- > DC inverter for TIG with advanced inverter technology to optimize arc performance.
- > Improved TIG Starting. Now starts DC(-) to maintain a sharp tungsten.
- Thermal overload protection with indicator light helps prevent machine damage if the duty cycle is exceeded or airflow is blocked.
- > 200 amps @ 60% duty cycle is the highest output rating in this machine class.
- Inverter-based, DC power source has a simple-to-use operator interface providing only the necessary controls in a compact machine.



PROCESSES

DC TIG (GTAW) MMA

INCLUDED

VT-2015 Machine Only Includes:

- ➤ VT-201S
- > 4M WP17 TIG TORCH.
- 2.5M work cable and clamp.







*Please note that the specification may vary within each country. Specifications are subjected to change without notice.

AUSTCORP MANUFACTURING SDN. BHD.

NO. 8 & 10 PERSIARAN BATU GAJAH PERDANA 3 TAMAN BATU GAJAH PERDANA 31550 PUSING PERAK MALAYSIA TEL: (605)3632 115 FAX: (605)3632 111

E-mail: austcorp@welding.com.my WEB: www.welding.com.my



Welding Technology