

DC TIG/MMA

VT-400i Advance

TIG/STICK Welding
Power Source

Quick Specs

Light Industrial Applications

Maintenance Repair
Shipboard Installation
Fabrication
Hobbyist
Process Piping

Power Voltage

3 Phase AC415V ±15%
50/60Hz

Input Current

17.25kVA

Output Current

15-400A
Max. OCV: 71VDC

Output Voltage

10.6V~26V

Duty Cycle

60%

Weight

19KG

Dimensions

D500×H445×W245MM

**Portable. Professional.
Rugged. Affordable.**

FEATURES

- DC inverter for TIG with advanced inverter technology to optimize arc performance.
- Improved TIG Starting. Now starts DC(-) to maintain a sharp tungsten.
- **Thermal overload protection with indicator light** helps prevent machine damage if the duty cycle is exceeded or airflow is blocked.
- 400 amps @ 60% duty cycle is the highest output rating in this machine class.
- Inverter-based, DC power source has a **simple-to-use operator interface** providing only the necessary controls in a compact machine.

PROCESSES

DC TIG (GTAW)
MMA



INCLUDED

VT-400i Machine Only Includes:

- VT-400i
- 6M WP18-2 TIG TORCH.
- 3M work cable and clamp.

INPUT



OUTPUT



**Please note that the specification may vary within each country. Specifications are subjected to change without notice.*

AUSTCORP MANUFACTURING SDN. BHD.

NO. 8 & 10 PERSIARAN BATU GAJAH PERDANA 3
TAMAN BATU GAJAH PERDANA
31550 PUSING PERAK MALAYSIA
TEL: (605)3632 115 FAX: (605)3632 111
E-mail: austcorp@welding.com.my
WEB: www.welding.com.my



Welding Technology